



EQUIPMENT REDEFINED.

TRADE FOCUSED. SYSTEM WIDE.

1 REDLITHIUM™ FORGE™ XC8.0 BATTERY PACK

FITS MX FUEL™
EQUIPMENT



REDLITHIUM
FORGE™

2 REDLINK PLUS™ INTELLIGENCE



3 LAST FUSE TECHNOLOGY



50 FUSES
REMAINING

MX FUEL™ Electrofusion Processor

UP TO **40%**
LIGHTER,
EASIEST TRANSPORT

INSTANT SETUP,
NO GENERATOR

FUSING
SIMPLIFIED

KIT INCLUDES: MXF545-0 Electrofusion Processor, 15' Electrofusion Leads, (1) MX FUEL™ REDLITHIUM FORGE™ XC8.0 Battery Pack, MX FUEL™ Rapid Charger, Barcode Scanner and (2) Fusion Tips

SPECIFICATIONS

Wireless Barcode Scanner	Yes (Fully Rechargeable)	Height	13.7"
Calibration	3 Years	Depth	23.9"
Calibration Lockout	Yes, with 90-Day Warning	Width	10.4"
GPS	Yes	Operating Temperature	0° F – 125° F
ONE-KEY™ Compatible	Customizable Reporting	Charge Time	65 Min (as configured)
Data Logging	Yes, USB or Wireless Download	Voltage Output	8V – 48V
Weight (w/ battery)	34 lbs	Badge Scanning	Yes (ISO 12176-3)
Fusion Tip Sizes	4 mm & 4.7 mm	Manual Barcode Entry	Yes
Lead Options	15 ft, Field Replaceable	Ambient Temperature Sensor	Yes
Warranty	2 Year Machine, 2 Year Battery	Coupling Compatibility	ISO 12176-2, ASTM F2897

STANDARDS

Meets: ISO 13950, ISO 12176-2, ISO 12176-3, ISO 12176-4, ASTM F2897, IEC 60335-1
Designation: P₂US₂VADX

RUN-TIME

Up to (2) 8" Fusions, (40) 2" Fusions, and (150) 3/4" Fusions*
(w/ Kitted MX FUEL™ REDLITHIUM™ FORGE™ XC8.0 Battery Pack)

*Estimates and variable based on ambient temperature.